

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA



Log No. 3123
 Rec. Sept. 12 1955
 Well No.
 Permit No.
Do not fill in

Owner BOB ROBERTS Driller Frank W. Parks
 Address Box 442 Yerrington, Nev. Address Box 202, Fernley, Nev. Lic. No. 224
 Location of well: 1/4 1/4 Sec. ²⁶, T. 13 N/S, R. 25 E, in Lyon County
 or about 1 mile south of Yerrington City Limits on Wellington road
 Water will be used for Domestic Total depth of well 90 ft.
 Size of drilled hole 8 inch Weight of casing per linear foot aprox. 12 lbs.
 Thickness of casing 10 guage Temp. of water 54 deg.
 Diameter and length of casing 8 in. ID 4ft lengths gas welded
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure.
 If nonflowing well give depth of standing water from surface 8 ft.
 If flowing well describe control works.
 (Type and size of valve, etc.)
 Date of commencement of well Aug. 10th 55 Date of completion of well Aug. 20th. 55
 Type of well rig Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	10	10	sand & clay, soft
10	75	65	sand, coarse & fine, quick
75	85	10	hard clay
85	90	5	coarse water gravel & rocks

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 85ft. to 90ft. ft.

Other aquifers 10ft. to 75ft. quick sand containing water

First water at 10ft. feet.

Casing perforated

from none to ft.

Size of perforations



