


# WELL LOG AND REPORT TO THE STATE

## ENGINEER OF NEVADA

### Eagle Springs Unit 58-26 Water Well #1

Log No. 3135  
 Rec. Sept 6 1955  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner Shell Oil Co. Driller J. D. Hill  
 Address Salt Lake City, Utah Address Ely, Nevada Lic. No. 14  
 Location of well: SW 1/4 SE 1/4 Sec. 26 9 X 57 Address Nye County \_\_\_\_\_  
 or 395.63' N and 2150.25' W. of SE Cor. Sec. 26  
 Water will be used for Oil well drilling (See note on reverse side) Total depth of well 90 feet  
 Size of drilled hole 6" Weight of casing per linear foot 20#  
 Thickness of casing 1/4 Temp. of water \_\_\_\_\_  
 Diameter and length of casing 1/4 x 61 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 3 feet  
 If flowing well describe control works \_\_\_\_\_ (Type and size of valve, etc.)  
 Date of commencement of well April 5, 1955 Date of completion of well April 8, 1955  
 Type of well rig Churn drill

#### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	17	17	sand
17	18	1	sand and gravel
18	35	17	sand and silt
35	36	1	sand and gravel
36	90	54	silt

Formation: Fluvial and Lacustrine deposits.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 17 to 18 ft.

Other aquifers  
35 36

First water at 17 feet.

Casing perforated  
 from 3 to 61 ft.

Size of perforations  
1/4 x 6

