

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3152  
 Rec. Sept 14 1955  
 Well No. \_\_\_\_\_  
 Perm. No. \_\_\_\_\_  
*Do not fill in*

Owner Joe Boggio Driller Johnson & McNinch  
 Address Paradise Valley, Nevada Address Box 585, Winnemucca, Nev No. 219  
 Location of well: 1/4 NW 1/4 Sec. 25, T. 42 N, R. 39 E, in Humboldt County  
 or about 100' south of Paradise Hotel on next block.  
 Water will be used for Domestic Total depth of well 100'  
 Size of drilled hole 8" Weight of casing per linear foot 13#  
 Thickness of casing 10 gauge Hard Red Steel Temp. of water Cold  
 Diameter and length of casing 8" 100'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 9'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well 29 August 1955 Date of completion of well 30 August 1955  
 Type of well rig #71 Speed Star Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Good black soil
10	19	9	Sand & clay
19	48	29	Granite sand
48	55	7	Gravel
55	90	35	Granite sand
90	100	10	Good clean gravel
			Bottomed hole in good gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 90 to 100 ft.

Other aquifers 48-55  
and surface water

---

First water at 19 feet.

Casing perforated

from 48' to 100' ft.

Size of perforations

1/8 X 1 1/2 slot

