

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3284
 Rec. Jan. 6 1956
 Well No. _____
 Permit No. _____

Do not fill in

Owner Mr. G. A. Portor Driller Bob Meyer
 Address G.D. Gardnerville, Nevada Address Carson City, Nevada Lic. No. 209
 Location of well: NE 1/4 ^W ~~SE~~ 1/4 Sec. ²⁷ ~~17~~, T14 N1/2, R. 20 E, in Douglas County
 or Homestead Two Miles North of Douglas-Tahoe Airport
 Water will be used for Domestic Total depth of well 60 1/2 Feet
 Size of drilled hole 6 Inch Weight of casing per linear foot 13 lbs
 Thickness of casing 3/16 " Temp. of water Cool
 Diameter and length of casing 6" ID, 60 feet 6 inches
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing
 If nonflowing well give depth of standing water from surface 31 feet
 If flowing well describe control works Not Flowing
 (Type and size of valve, etc.)
 Date of commencement of well December 30, 1955 Date of completion of well January 4, 1956
 Type of well rig 71 Speed Star, Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Sand
15	26	11	Sand, Rock & Clay
26	42	16	Clay & Small Solk Rock
42	57	15	Sand & Gravel
57	60	3	Rock & Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 43 to 57 ft.

Other aquifers.....

None

First water at 43 feet.

Casing perforated

from 30 to 60 ft.

Size of perforations

1/8" X 6"



