

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3883  
 Rec. April 25 1956  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Dr. J. L. Mayo Driller Louis Clark  
 Address Tooele Utah Address Elko Nev Lic. No. 4

Location of well: SE 1/4 SE 1/4 Sec. 14, T37N/S, R69E, in Elko County

Water will be used for Domestic Total depth of well 110

Size of drilled hole 6" Weight of casing per linear foot 19 lbs.

Thickness of casing 5/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 6" 110'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 55 ft

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 3-27-56 Date of completion of well 3-29-56

Type of well rig Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
	40	40	Grey clay
40	62	22	Yellow sandy clay
62	73	11	Gravel and sand
73	110	37	Yellow sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 62 to 73 ft.

Other aquifers \_\_\_\_\_

First water at 62 feet.

Casing perforated

from 73 to 107 ft.

Size of perforations

1/8 x 5"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 48 gals. per min. at 63 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Louis Clarkson  
Well Driller

By N. H. Math

License No. 211

Dated April 23, 1956

(Not to be filled in by Driller)

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

OFFICE  
STATE ENGINEER

1956 APR 25 AM 9 51