WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3887
Rec. May 3. 1956
Well No.
Permit No.
Do not fill in

Owner: George Pomeroy Driller: Fred Erb
Address: Fallon Nevada Address: E. Star Rt. Fallon Nev. Lic. No. 121

Location of well: S.E. ¼ N.E. ¼ Sec. 31, T. 19 N/S, R. 29 E, in Churchill County

or

Water will be used for: Domestic Total depth of well: 32 ft.

Size of drilled hole: 6 inch Weight of casing per linear foot

Thickness of casing: 20 gauge Galvinized Temp. of water: 60 degrees

Diameter and length of casing: 6 inch Casing 32 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 10 feet

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: April 2-1956 Date of completion of well: April 10, 1956

Type of well rig: Cable Tool Well Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Sand
10	20	10	adobe
20	26	6	Silt.
26	32	6	Water Sand

Water-bearing Formation, Casing Perforations, Etc.
Water Sand

Chief aquifer (water-bearing formation)
from 26 to 32 ft.

Other aquifers

First water at 10 feet.

Casing perforated
from 26 to 32 ft.

Size of perforations
1 X 1/64 inch

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 in	0	32	32	20 gauge Galvinized Casing & Cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump Test about 800 gallons per Hour.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Erb
Well Driller

By Mrs Fred Erb

License No. 121

Dated April 12, 1956

OFFICE
STATE ENGINEER

1956 MAY 2 AM 10 46

(Not to be filled in by Driller)