

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3467
 Rec. July 2 1957
 Well No. _____
 Permit No. 18535

Do not fill in

Owner Dewey Dann Driller Carruthers Drilling Service
 Address Beowawe, Nevada Address Beowawe, Nevada Lic. No. 116
 Location of well: NE 1/4 Sec. 33, T. 29 N, R. 49 E, in Eureka County
 or _____
 Water will be used for Irrigation Total depth of well 228
 Size of drilled hole 14" Weight of casing per linear foot Dble 10#
 Thickness of casing Dble 10# Temp. of water Cool
 Diameter and length of casing 14 3/8
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure. _____
 If nonflowing well give depth of standing water from surface. _____
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well April 25th 1956 Date of completion of well May 30th 1956
 Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Surface
6	12	6	Gravel
12	45	33	Clay
45	58	13	Sandy Clay
58	70	12	Coarse Sand (Water)
70	78	8	Sticky Clay
78	86	8	Clay
86	89	3	Sand
89	95	6	Sandy Clay
95	98	3	Sand
98	114	16	Sandy Clay
114	125	11	Hard Fine Surface
125	132	7	Sandy Clay
132	136	4	Sticky Clay
136	142	6	Hard Sand
142	147	5	Silty Clay
147	150	3	Decomposed Granite
150	162	12	Sandy Clay
162	167	5	Hard Fine Sand
167	181	14	Coarse Sand
171	175	4	Sandy Clay
175	177	2	Decomposed Granite
177	180	3	Silty Sand
180	188	8	Decomposed Granite
188	202	14	Clay
202	214	12	Sandy Clay
214	218	4	Decomposed Granite
218	228	10	Sandy Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 58 to 70 ft.

Other aquifers 86-89

95-98 114-125 147-150

162-171 175-177

180-188 214-218

First water at 55 feet.

Casing perforated

from 55 to 218 ft.

Size of perforations

1/2"x3" Slots

