

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3495
 Rec. July 27 1956
 Well No.
 Permit No.

Do not fill in

Owner Pete Pedrolì Driller Johnson & McNinch

Address Winnemucca Nevada Address Winnemucca Nevada Lic. No. 919

Location of well: NE 1/4 Ne 1/4 Sec 24, T36 N/S, R38 E, in Humboldt County

Water will be used for Stock water Total depth of well 36'

Size of drilled hole 8" Weight of casing per linear foot 15 LBS.

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 8" 36'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface..... 8'

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well July 1, 1956 Date of completion of well July 2, 1956

Type of well rig # 7I Speed Star cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	topsoil and clay
12	24	12	hard dry clay & rocks
24	36	12	fine gravel and sand bottomed on blue lime bed rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 24 to 38 ft.

Other aquifers.....

First water at 24 feet.

Casing perforated
 from 20 to 36 ft.

Size of perforations
1/8 X 3 torch slots



