

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 3576
 Rec. Aug. 22 19 56
 Well No. _____
 Permit No. 44922
Do not fill in

Owner GAMBLE RANCHES INC. Driller BOLEY, HENRY, WEE CH

Address MONTELLIO NEV. Address MURTAUGH, IDAHO Lic. No. 240

Location of well: NE 1/4 NW 1/4 Sec. 21, T. 40N, R. 6E, in ELKO County
 or Stewart Well

Water will be used for LIVE STOCK Total depth of well 200 FEET

Size of drilled hole 6" Weight of casing per linear foot 9.7

Thickness of casing 10 GA. Temp. of water COLD

Diameter and length of casing 6" I.D.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 98"

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well AUG. 14, 1956 Date of completion of well AUG. 16, 1956

Type of well rig SPUDDER (150 KEYSTONE)

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	22	22	BROWN DIRT & ROCKS
22	147	125	TAN CLAY
147	155	8	GREY LIMESTONE
155	166	11	WHITE SANDSTONE
166	187	21	TAN CLAY
187	200	13	GREY SANDSTONE

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 145 to 155 ft.

Other aquifers NONE

First water at 145 feet.

Casing perforated

from 145 to 155 ft.

Size of perforations

4" x 1/8"



