Nev. Copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

HITCHING POST MOTEL

Log No. 3538
Rec. Sept. 27 1956
Well No.
Permit No. 16770
Do not fill in

Owner E. T. Nollner Driller Phelps Pump and Equipment

Address Address 400 College, No. L. V. Lic. No. 98

Location of well: NE ¼ SE ¼ Sec. 7, T. 20 N, S, R 62 E. in Clark County

or

Water will be used for Commercial Total depth of well 150'

Size of drilled hole 12" Weight of casing per linear foot 11.06#

Thickness of casing 10 Ga. Temp. of water Approx. 68 degrees

Diameter and length of casing 150 ft. of 8" O.D. casing
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 85'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 6/29/56 Date of completion of well 8/10/56

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Gravel and Clay
18	20	2	Clean Gravel
20	40	20	Red clay
40	60	20	Gravel and Clay
60	75	15	White Clay
75	85	10	Clay
85	92	7	Gravel and Clay(~~xxxxx~~)
92	97	5	Water Sand and Gravel (Water)
97	120	23	Red Clay
120	122	2	Gravel and Sand
122	150	27	Clay

Water-bearing Formation, Casing Perforations, Etc

Chief aquifer (water-bearing formation)

from 92 to 97 ft

Other aquifers

120-122

First water at 92 feet.

Casing perforated

from 85 to 130 ft.

Size of perforations

Torch

(OVER)