WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3571
Rec. Nov. 23 1956
Well No.
Permit No.
Do not fill in

Owner: E. A. Cope
Driller: Harvey Meyer
Address: New Empire
Address: Carson City, Nevada
Lic. No. 10

Location of well: NW ¼ SE ¼ Sec. 29, T. 16 N/S, R. 20 E, in Ormsby County

or New Empire

Water will be used for: Domestic
Total depth of well: 74 feet

Size of drilled hole: 6 Inch
Weight of casing per linear foot: 13 lbs.

Thickness of casing: 3/16 Inch
Temp. of water: Cool

Diameter and length of casing: 6" ID, 74 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: Not Flowing

If nonflowing well give depth of standing water from surface: 10 feet

If flowing well describe control works: Not Flowing
(Type and size of valve, etc.)

Date of commencement of well: September 3, 1956
Date of completion of well: September 4, 1956

Type of well rig: 72 Speed Star, Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Sand & Clay
20	25	5	Sand with Water
25	40	15	Sand & Clay
40	55	15	Water Sand
55	74	19	Sand & Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 40 to 55 ft.

Other aquifers
20' to 40'

First water at 20 feet.

Casing perforated
from 50 to 74 ft.

Size of perforations
1/8" X 6"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6" ID	0	74	74	Star Drive Shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well will make 1800 gal per hour bailing test.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Bob Meyer
Well Driller

By Bob Meyer

License No. 10

Dated November 20, 19 56

(Not to be filled in by Driller)

OFFICE
ENGINEER
1956 NOV 23 AM 8 09