WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3590
Rec. Dec. 4 1956
Well No.
Permit No.
Do not fill in

Owner: Mike Cota Driller: Fred Erb
Address: Fallon Nevada Address: E. Star St. Fallon Nev. Lic. No. 121
Location of well: N.W. 1/4 N.W. 1/4 Sec. 33, T. 19 N/S, R 29 E, in Churchill County
or

Water will be used for: Domestic Total depth of well: 30 ft.
Size of drilled hole: 6 inch Weight of casing per linear foot:
Thickness of casing: 20 gauge Galvanized Temp. of water: 60°
Diameter and length of casing: 6 inch casing 30 ft long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:
If nonflowing well give depth of standing water from surface: 7 ft.
If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Nov. 12-56 Date of completion of well: Nov 13-1956
Type of well rig: Cable Tool well Rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	loam
7	14	7	adobe
14	30	16	Sand

Water-bearing Formation, Casing Perforations, Etc.
Sand

Chief aquifer (water-bearing formation)
from 14 to 30 ft.

Other aquifers

First water at 7 feet.

Casing perforated
from 24 to 30 ft.

Size of perforations
1/64 X 1 inch

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 in.	0	30	30 ft.	20 gauge Galvinized Casing + Cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump. Test about 18 gal. per Hr

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Esb.
Well Driller

By Mrs Fred Esb

License No. 121

Dated Dec 3, 19 56

Well Drilling Contractor
Lic. No. 4732

(Not to be filled in by Driller)