WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3616
Rec. Dec. 13 1956
Well No.
Permit No.
Do not fill in

Owner: Roy Visbeck — Driller: J. B. Reynolds

Address: Austin — Address: Fallon — Lic. No. 28

Location of well: ¼ ¼ Sec. 3, T. 17N/S, R. 42E, in Lander County

or stockwell no. 4

Water will be used for: stock water — Total depth of well: 70'2"

Size of drilled hole: 8" — Weight of casing per linear foot: 18#

Thickness of casing: .188 — Temp. of water: cold

Diameter and length of casing: 8" X 70'2"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 20 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: Nov. 15, 1956 — Date of completion of well

Type of well rig: cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	silt
12	30	18	gravel
30	35	5	clay
35	38	3	gravel
38	55	17	clay
55	70	15	gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 55 to 70 ft.

Other aquifers
35 - 38

First water at 35 feet.

Casing perforated
from 46 to 70 ft.

Size of perforations
1/8"X2"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. D. Reynolds
Well Driller

By.....

License No. 28

Dated Dec. 12, 19 56

OFFICE
STATE ENGINEER

1956 DEC 13 AM 11 16

(Not to be filled in by Driller)