

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3620  
 Rec. Dec. 24 1956  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Frances E. Dalton Driller Harvey & Bob Meyer  
 Address 20 East 86 St. New York, X N. Y. Address 206 Bath St. Carson City Lic. No. 10 209  
 Location of well: SW 1/4 SE 1/4 Sec. 11, T. 15 N/S, R. 19 E, in Ormsby County  
 or Barrows Place, Ash Canyon  
 Water will be used for Domestic Total depth of well 253 feet  
 Size of drilled hole 8" to 121, 6" to 253 feet Weight of casing per linear foot 13 lbs  
 Thickness of casing 3/16" Temp. of water Cool  
 Diameter and length of casing 6" ID, 253 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing  
 If nonflowing well give depth of standing water from surface 183 feet  
 If flowing well describe control works Not Flowing  
(Type and size of valve, etc.)  
 Date of commencement of well November 9, 1956 Date of completion of well December 19, 1956  
 Type of well rig 71 Speed Star ( Cable Tools )

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	80	78	Clay & Gravel
80	121	41	Clay & Granet Bolders
121	126	5	Solid Granet
126	220	94	Clay & Granet Bolders
220	240	20	Gravel & Granet Bolders
240	253	13	Fine Sand & Granet Bolders

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 220 to 253 ft.

Other aquifers.....  
None

---

First water at 220 feet.

Casing perforated  
 from 200 to 253 ft.

Size of perforations  
1/4" X 6"



# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3620  
 Rec. Dec 24 1956  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner Frances E. Dalton Driller Harvey & Bob Meyer  
 Address 20 East 86 St. New York, X N. Y. Address 206 Bath St. Carson City Lic. No. 10 209  
 Location of well: SW 1/4 SE 1/4 Sec. 11., T. 15 N/S, R. 19 E, in Ormsby County  
 or Barrows Place, Ash Canyon  
 Water will be used for Domestic Total depth of well 253 feet  
 Size of drilled hole 8" to 121, 6" to 253 feet Weight of casing per linear foot 13 lbs  
 Thickness of casing 3/16" Temp. of water Cool  
 Diameter and length of casing 6" ID, 253 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing  
 If nonflowing well give depth of standing water from surface 183 feet  
 If flowing well describe control works Not Flowing  
(Type and size of valve, etc.)  
 Date of commencement of well November 9, 1956 Date of completion of well December 19, 1956  
 Type of well rig 71 Speed Star (Cable Tools)

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	80	78	Clay & Gravel
80	121	41	Clay & Gravel Bolders
121	126	5	Solid Granet
126	220	94	Clay & Granet Bolders
220	240	20	Gravel & Granet Bolders
240	253	13	Fine Sand & Granet Bolders

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 220 to 253 ft.

Other aquifers.....

None

---

First water at 220 feet.

Casing perforated

from 200 to 253 ft.

Size of perforations

1/4" X 6"

