

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 3653  
 Rec. Jan. 27 1957  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Richard Graves Driller Harvey & Bob Meyer

Address 512 Mountain St. Carson City, Nev. Address 306 Bath St. Carson City Lic. No. 10

Location of well: NW 23 SE 1/4 NW 1/4 23 18 19 Sec. 27, T. 16 N/S, R. 19 E, in Washoe County  
 or Pine Cone Road, Lake Tahoe, Nevada

Water will be used for Domestic Total depth of well 55 feet

Size of drilled hole 8" Weight of casing per linear foot 18 lbs

Thickness of casing 3/16" Temp. of water Cool

Diameter and length of casing 6" ID, 55 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing

If nonflowing well give depth of standing water from surface 15 feet

If flowing well describe control works Not Flowing  
 (Type and size of valve, etc.)

Date of commencement of well December 26, 1956 Date of completion of well January 2, 1957

Type of well rig 72 Speed Star Bable Tools

### LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|------------------|
| 0         | 22      | 22             | Clay & Rock      |
| 22        | 30      | 8              | Sand w/water     |
| 30        | 48      | 18             | Clay & Sand      |
| 48        | 55      | 7              | Bolders & Sand   |

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 48 to 55 ft.

Other aquifers.....

---

First water at 22 feet.

Casing perforated  
 from 35 to 55 ft.

Size of perforations  
1/8" X 6"

