

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3689  
 Rec. March 12, 1957  
 Well No. 16747  
 Permit No. 16747

23469 Do not fill in  
 28750

Owner Giovanni Carri Driller William Flynn  
 Address Paradise Valley, Nevada Address Box 26 Sutter Calif. Lic. No. 162  
 Location of well: NE 1/4 SW 1/4 Sec. 20, T. 42 N. 18, R. 40 E, in Humboldt Co., County  
 or Carri Ranch, Four miles north east of Paradise Valley, Nevada  
 Water will be used for Irrigation and Domestic Total depth of well 670 Ft.  
 Size of drilled hole 16" Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 3/16" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 16" 306'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 15'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well May 1, 1955 Date of completion of well March 5, 1957  
 Type of well rig Cable

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Soil
8	16	8	Cemented Gravel
16	36	20	Gravel-Clay
36	44	8	Gravel slightly loose
44	72	28	Gravel-Clay
72	78	6	Cemented Gravel slightly loose
78	102	24	Gravel-Clay
102	124	24	Cemented Gravel Slightly loose
124	138	13	Cemented gravel tight
138	150	12	Cemented gravel slightly loose
150	172	22	Brown soft clay Dry
172	<del>185</del> 185	13	Cemented gravel slightly loose
185	195	10	Cemented gravel tight
195	215	20	Brown clay sand and gravel
215	230	15	Brown clay
230	245	15	Gravel-Course
245	250	5	Brown Clay
250	292	42	Brown gravel clay
292	306	14	sand & gravel loose
306	348	34	Brown clay
340	365	25	Cemented gravel
365	390	25	gravel-clay
390	442	52	Cemented sand & Gravel
442	475	33	Gravel-clay
475	510	35	San & Gravel cemented

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from None to \_\_\_\_\_ ft.

Other aquifers \_\_\_\_\_

First water at \_\_\_\_\_ feet.

Casing perforated  
from 40 to 300 ft.

Size of perforations

3/8" x 2 1/2"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
510	525	15	Gravel-clay
525	540	15	Sand & Gravel cemented
540	575	35	Gravel-clay
575	605	30	sand & gravel cemented
605	635	30	Brown clay
635	670	35	Sand & gravel loose sand in bottom

CASING RECORD

Diam. casing	From feet	To feet	Length	Remarks—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

---



---



---



---



---



---

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Wm F Lynn  
Well Driller

By.....

License No. 162

Dated Mar 7, 19 57

(Not to be filled in by Driller)

---



---



---



---



---



---



---



---



---



---