WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Basin #110k

Log No. 3702
Rec. April 4 1957
Well No.
Permit No.
Do not fill in

Owner John Baxter Driller Fred Erb

Address Schurz Nevada Address E. Star Rt. Fallon, Nev. Lic. No. 121

Location of well S½ N.E¼ N.E¼ Sec. 35, T. 13 N/S, R 28 E, in Mineral Co. County

or

Water will be used for Domestic Total depth of well 34 ft.

Size of drilled hole 6 Inches Weight of casing per linear foot

Thickness of casing 10 gauge red heart steel Temp. of water 61 degrees

Diameter and length of casing 6 inch casing 34 ft. long
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 12 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well March 28, 1957 Date of completion of well March 29, 1957.

Type of well rig Cable type well rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	Adobe
12	20	8	Sand
20	22	2	Adobe
22	34	12	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Gravel

Chief aquifer (water-bearing formation)

from 22 to 34 ft.

Other aquifers

First water at 12 feet.

Casing perforated

from 22 to 34 ft.

Size of perforations

1/64 X 1 Inch

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 In.	0	34	34	10 gauge red heart steel

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump test about 1500 gallons per hour

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Eisele
Well Driller

By Mrs Fred Eisele

Well Driller3### License No. 121

Dated April 2, 1957

Contr. Lic. No. 4732

OFFICE
STATE ENGINEER

1957 APR 5 AM 10 16

(Not to be filled in by Driller)