


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3776  
 Rec. May 23 1957  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_



Owner FRANK SIMON APRI Driller H. E. HANSON  
 Address FISH LAKE TONOPAH NV Lic. No. 113  
 Location of well: EAST 1/4 1/4 Sec. 16 T. 35 N. S. R. 1 E. in RANGE 135 E. N. D. M. Count  
 or SE 1/2 NE 1/4 Sec 16 T. 35 R. 135 E. N. D. M.  
 Water will be used for stock & irrigation Total depth of well 68'  
 Size of drilled hole 14" Weight of casing per linear foot 129A  
 Thickness of casing \_\_\_\_\_ Temp. of water 62°  
 Diameter and length of casing 12" x 68'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface \_\_\_\_\_  
 If flowing well describe control works ground pack well No control  
 (Type and size of valve, etc.)  
 Date of commencement of well Dec 27-55 Date of completion of well April 1-57  
 Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Top soil + clay
25	39	14	sand + gravel
39	65	26	PACK SAND
65	68	3	clay

Water-bearing Formation, Casing Perforations, Etc.  
 Chief aquifer (water-bearing formation)  
 from 25 to 65 ft.  
 Other aquifers \_\_\_\_\_  
 First water at 25 feet.  
 Casing perforated  
 from 18 to 66 ft.  
 Size of perforations  
1/4 x 1 1/2"

OFFICE  
 STATE ENGINEER  
 1957 MAY 23 AM 10 19

