WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3784
Rec. 6-13- 19 57
Well No.
Permit No.
Do not fill in

Owner: Mission of St. Mary the Virgin
Address: Wadsworth.
Driller: J N Pitcher Co C Wiley
Address: 190 Moana Lane Lic. No. 261

Location of well: SE ¼ NE ¼ Sec. 10, T. 20 N/S, R. 24 E, in Churchill County
or

Water will be used for: Domestic
Total depth of well: 56
Size of drilled hole: 6"
Weight of casing per linear foot: 12#
Thickness of casing: 3/16
Temp. of water: 60
Diameter and length of casing: 6 5/8 X 54'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 40
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: April 16
Date of completion of well: April 19-57
Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	31	31	Sand & Cobblestone
11	31	20	Washed Cobblestone
31	41	10	Sand
41	52	11	Sand W/water
52	56	4	Clay & gravel

OFFICE
STATE ENGINEER

1957 JUN 13 AM 9 59

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 41 to 52 ft.
Other aquifers

First water at 41 feet.

Casing perforated
from 40 to 54 ft.

Size of perforations
1/8 X 5 - 5 rows
Torch cuts

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6 1/8	2	56	54	Black iron— Heavy Drive Shoe weld on.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail Test 10 G.P.M. 2' DD.
Heavy Run of Fine Sand.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [signature] Patcher Co
Well Driller

By [signature]

License No. 265

Dated April 19, 1957

(Not to be filled in by Driller)