WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3786
Rec. June 21 19 57
Well No.
Permit No.
Do not fill in

Owner: C. D. Pickrell Driller: J. C. Faretto & Son
Address: Rt 1, Box 837 Reno, Nev. Address: 736 Humboldt St, Reno Lic. No. 2
Location of well: N.W ¼ ¼ Sec. 34, T. 18 N/S, R 20 E, in Washoe County
or 1 mile north east Steamboat Springs on the old Virginia Rd.
Water will be used for: Domestic Total depth of well: 86 ft.
Size of drilled hole: 6 inch Weight of casing per linear foot: 18.97 Lbs
Thickness of casing: .280 of an inch Temp. of water: 60°
Diameter and length of casing: 6" inside diam. 8'-00" to 16'-04" lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 37'-00"
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: June 6, 1957 Date of completion of well: June 14, 1957
Type of well rig: 71 Speed Star Cable Tool Rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Yellow red clay with rocks & coarse sand,
20	45	25	Yellow red clay with coarse sand & gravel,
45	50	5	1st water. Yellow red clay with medium sand, stony & gravel,
50	55	5	Yellow clay with fine sand,
55	65	10	2nd water. Water-level 40'-00", Little water. Yellow clay with medium to coarse sand & gravel, stony,
65	86	21	Yellow clay. Soft,
86	92	6	3rd water. Water level 37'-00". Yellow

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 86 to 92 ft.
Other aquifers: 55 to 65
45 to 50

First water at 45 feet.

Casing perforated
from 55 to 65 ft.

Size of perforations
3/8" x 1 1/2"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
			clay with fine to coarse sand & coarse gravel, stony. Loose.

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0'-05"	80'-00"	80'-05"	Standard black pipe. Welded with ¼" x 3" couplings. Short pattern drive shoe. Perforated with Mills perforator,

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Clay formation. Sand & gravel black, tan, light & brown in color. Sharp edged, angular, some worn & smooth. Well cleaned & tested with bailer 4 gal per minute c8 ft drawdown.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. C. Faretto & Son
Well Driller

By Harold J. Faretto

License No. 2

Dated June 19, 1957

(Not to be filled in by Driller)

1957 JUN 21 AM 10 12

STATE ENGINEER
OFFICE