Ist Well at Silver Springs Nev. in 1957 By F.W.Parks

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3860
Rec. Aug. 8 19 57
Well No.
Permit No.
Do not fill in

Owner: Leroy Gardner — Driller: Frank W.Parks

Address: Silver Springs, Nev. — Address: Box 202 Silver Sprgs. Nev. — Lic. No. 224

Location of well: ¼ ¼ Sec. 20?, T. 17 N/S R. 23 E, in Lyon County

or about 7 mi. south & 3 mi. east in plot 4 S.Springs subdivision

Water will be used for: Domestic — Total depth of well: 100 ft.

Size of drilled hole: 6 in. — Weight of casing per linear foot:

Thickness of casing: 10 gauge — Temp. of water: Cold

Diameter and length of casing: 6 inch
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 34 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: June 15th 1956 — Date of completion of well: July 1st 1957

Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Sand & clay
18	40	22	clay & some sand hard
40	42	2	thin strata water & sand
42	60	18	sand
60	90	30	sand & clay hard
90	96	6	clay
96	100	4	coarse sand & gravel water chief aquifier

OFFICE
STATE ENGINEER

1957 AUG 8 AM 10 13

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 40ft. to 42ft ft.

Other aquifers 96ft to 100ft
coarse sand & gravel
chief acuifier

First water at 40ft. feet.

Casing perforated
from 98ft to 100ft ft.

Size of perforations
one/eiths inch wide
one &one/half inch long

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6in,	0	100	100	spiralweld 10 gauge casing 2ft by 2ft. concrete slab around casing at top of well casing 18in. above top of ground

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well pumped with hand pump with tail pipe setting at about 50 ft. below surface of ground, pump down level at about 150 gals. per hr. 7ft. recovery to normal ststic level about 5 min.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Frank W. Parks
Well Driller

By Frank W Parks

License No. 224

Dated July 7th, 19 57

(Not to be filled in by Driller)