

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3888
 Rec. 9-25 19 57
 Well No.
 Permit No. 25352
Do not fill in

Owner Hollman Mineral & Chemical Corp. Driller William B. Wright
 Address 4411 Angelo Dr. Beverly Hills, Cal Address Dyer, Nev Lic. No. 56
 Location of well: NW 1/4 NW 1/4 Sec. 11, T. 1 N/S, R. 23 E, in Trail Canyon Esmeral Count
 or Trail Canyon B&B Mine
 Water will be used for Mining Total depth of well 170 ft
 Size of drilled hole 18" Weight of casing per linear foot 10 lb
 Thickness of casing 10 ga Temp. of water 48
 Diameter and length of casing 10 id 16 ft lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....
 If nonflowing well give depth of standing water from surface 15 ft
 If flowing well describe control works.....
(Type and size of valve, etc.)
 Date of commencement of well 6. 7. 57 Date of completion of well 6. 30. 57.
 Type of well rig rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
top	33	33	sand rock gravel & clay
33	45	12	boulders sand & gravel
45	48	3	sand & gravel
48	70	22	clay & boulders
70	88	18	clean sand gravel & rock
88	100	12	boulders & clay
100	106	6	yellow clay
106	118	12	hard brown rock
118	126	8	gravel & rock
126	140	14	loose brown rock or shale
140	152	12	brown clay some volcanic formation
152	167	25	brown clay and rock
167	170	3	volcanic gravel & ash

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 33 to 45 ft.

Other aquifers 70 to 88
118 to 140

First water at 33 feet.

Casing perforated

from 45 to 150 ft.

Size of perforations
machine made

OFFICE
STATE ENGINEER

1957 SEP 25 AM 9 54



