

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

✓ Log No. 3914
 Rec. Oct. 21 1957
 Well No. _____
 Permit No. _____
Do not fill in

Owner George Koch Driller Harvey & Bob Meyer
 Address General Delivery, Carson City Address 306 Bath St. Carson Lic. No. 10
 Location of well: NW 1/4 NW 1/4 Sec 30, T. 14 N/S, R 20 E, in Douglas County
 or Jacks Valley Road
 Water will be used for Domestic Total depth of well 170
 Size of drilled hole 6" Weight of casing per linear foot 13 Lbs
 Thickness of casing 3/16 Inch Temp. of water Cool
 Diameter and length of casing 6" ID, 170 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing
 If nonflowing well give depth of standing water from surface 120 feet
 If flowing well describe control works Not Flowing
(Type and size of valve, etc.)
 Date of commencement of well August 28, 1957 Date of completion of well September 4, 1957
 Type of well rig 24-L, Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	Rock & Hard Pan
35	130	95	Clay & Sand
130	155	25	Gravel & Sand
155	170	15	Gravel

HARVEY & BOB MEYER
OFFICE DRILLING CONTRACTORS
STATE ENGINEER CARSON CITY, NEVADA

1957 OCT 21 AM 10 02

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 120 to 170 ft.

Other aquifers.....

First water at 120 feet.

Casing perforated
from 140 to 170 ft.

Size of perforations
1/8" X 6"



