WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3930
Rec. Nov. 12, 1957
Well No.
Permit No.
Do not fill in

Owner: Mr. Raymond Holmes — Driller: William Flynn

Address: 1735 Plumas St. Reno, Nev. — Address: Box 26 Sutter, Calif. — Lic. No. 162

Location of well: ¼ ¼ Sec. 1, T. 35 N/S, R. 37 E, in Humboldt Co. County

or 1 1/2 mi. west of Winnemucca on Hwy.40 , 100 ft. north of Hwy.

Water will be used for: Domestic — Total depth of well: 135

Size of drilled hole: 10 inch — Weight of casing per linear foot: 18 lb.

Thickness of casing: 3/16 in. — Temp. of water: Cold

Diameter and length of casing: 10 in.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 26 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Sept 20 57 — Date of completion of well: Sept 28 57

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	white sand
3	35	32	blue sand
35	60	25	blue sand pea gravel
60	110	50	blue fine sand
110	127	17	hard blue sand
127	135	8	yellow clay
135			large gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 135 to ft.

Other aquifers

First water at 70 feet.

Casing perforated

from to ft.

Size of perforations

1957 NOV 12 AM 9 17
STATE ENGINEER
OFFICE

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
10"	0	130	130	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well pumped 100 G.P.M. at 60 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [signature] Well Driller

By

License No. 162

Dated Sept 30, 19 57

(Not to be filled in by Driller)