

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3942  
 Rec. Dec. 6 1957  
 Well No. ....  
 Permit No. 14977  
*Do not fill in*

Owner Buckie A. Mauldin Driller Dave McNinch  
 Address Tenabo, via Beowawe, Nevada Address Winnemuc, ca, Nevada Lic. No. 219

Location of well: NE 1/4 NE 1/4 Sec. 25, T28 N/S, R. 47E, in Lander County

Water will be used for Irrigation Total depth of well 150'

Size of drilled hole 15 1/2" Weight of casing per linear foot 23 lbs.

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 15" 100'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 21 ft.

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well Nov. 20 1957 Date of completion of well Nov. 27, 1957

Type of well rig # 71 Speed Star cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	light soil
4	18	14	white clay
18	21	3	sand and fine gravel
21	28	7	clay
28	36	8	loose clean gravel
36	44	8	clay and broken gravel
44	51	7	loose clean gravel
51	80	29	clay
80	84	4	sandy clay
84	90	6	broken gravel
90	106	16	Sand and fine gravel
106	150	44	sand and sandy clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 90 to 106 ft.

Other aquifers 44 to 51  
28 to 36 18 to 21

---

First water at 21 feet.

---

Casing perforated

from 40 to 106 ft.

---

Size of perforations

1/4 x 3" slots  
 approx. 40 per ft.



