WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3943
Res. Dec. 10 1957
Well No.
Permit No.

Owner Louis Adams Driller Floyd Hastings

Address Logandale, Nevada Address Hurricane Utah Lic. No. 150

Location of well: ¼ ~~NW~~ ¼ Sec. ~~8~~ 22, T. ~~17~~ 15 ~~N~~/S, R. ~~67~~ 67 E, in Clark County

or Muddy River

Water will be used for Domestic Purposes Total depth of well 120'

Size of drilled hole 6 inch Weight of casing per linear foot 9 lbs.

Thickness of casing 9 gauge Temp. of water

Diameter and length of casing 6" — 120'
(Casing 10" in diameter and under give inside diameter; casing 10" in diameter give outside diameter)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 21'

If flowing well describe control works (Type and size of valve, etc.)

Date of commencement of well 11/12/57 Date of completion of well 11/14/57

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	36	36	Sandy Clay
36	50	14	Clay
50	66	6	Clay + Gravel
66	80	14	Clay
80	83	3	Gravel
83	86	3	Clay
86	89	3	Gravel
89	102	13	Clay
102	107	5	Sand + Gravel
107	120	13	Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 102 to 107 ft.

Other aquifers 50-66

86-83 86-89

First water at 36 ft.

Casing perforated

from 80 to 107 ft.

Size of perforations

¼" x 2"

1957 DEC 10 AM 3 58

[illegible] ENGINEER

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6	0	120	120	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Floyd Hastings
Well Driller

By [illegible]

License No. 150

Dec 6, 1957

(Not to be filled in by Driller)

DEC 10 PM 3 26
OFFICE
STATE ENGINEER