WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 3946
Rec. Dec 10 19 57
Well No.
Permit No.
Do not fill in

Owner Logandale City & Clark County Driller Floyd Hastings
Address Logandale Nevada Address Hurricane Utah Lic. No. 150

Location of well: ¼ SW¼ Sec. 26, T. 15 S/S, R 67 E, in Clark County

or

Water will be used for Sprinkling Cemetary Total depth of well 100'

Size of drilled hole 6" Weight of casing per linear foot 9 lbs.

Thickness of casing 9 gauge Temp. of water

Diameter and length of casing 6" — 100'
(Casing 18" in diameter and under give inside diameter; casing 18" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 22'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 11/14/57 Date of completion of well 11/21/57

Type of well rig

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sand
8	20	12	Boulders
20	30	10	Conglomerate
30	50	20	Gravel
50	100	50	Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 30' to 50' ft.

Other aquifers

First water at 30 feet

Casing perforated

from 30' to 50' ft.

Size of perforations

¼" X 2"

DEC 10 PM 3 59

(OVER)

910

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	100	100	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Floyd Hastings
Well Driller

By [illegible]

License No. 150

Dec 6, 1951

(Not to be filled in by Driller)

'57 DEC 10 PM 3 [illegible]
STATE ENGINEER
OFFICE