

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4010
 Rec. Feb. 21 1958
 Well No. _____
 Permit No. _____

Do not fill in

Owner Glen D. Knight Driller Harvey & Bob Meyer

Address Box 30 Steamboat, Nevada Address 306 Bath St. Carson Lic. No. 10

Location of well: NW 1/4 SE 1/4 Sec. 11, T. 17 N/S, R. 19 E, in Washoe County
 or West Side of Washoe Lake

Water will be used for Domestic Total depth of well 63 feet

Size of drilled hole 6 Inch Weight of casing per linear foot 13#

Thickness of casing 3/16 Inch Temp. of water Cool

Diameter and length of casing 6" ID, 63 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing

If nonflowing well give depth of standing water from surface 25 feet

If flowing well describe control works Not Flowing
(Type and size of valve, etc.)

Date of commencement of well February 4, 1958 Date of completion of well February 6, 1958

Type of well rig 71 Speed Star

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material | Water-bearing Formation, Casing Perforations, Etc. |
|-----------|---------|----------------|--------------------|---|
| 0 | 8 | 8 | Sticky Clay | |
| 8 | 46 | 38 | Clay & Sand | Chief aquifer (water-bearing formation) from <u>46 ft</u> to <u>63</u> ft. |
| 46 | 63 | 17 | Yellow Clay & Sand | Other aquifers..... |

**HARVEY & BOB MEYER
DRILLING CONTRACTORS
CARSON CITY, NEVADA**

First water at 26 feet.

Casing perforated
from 33 to 63 ft.

Size of perforations
1/8" X 6"

Torck

