Not Copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4021
Rec. Mar. 5 1958
Well No.
Permit No. ~~15964~~ DLE
Do not fill in

Owner N.O.Berry. Driller Enloe Drilling Co.

Address Sacramento, Calif. Address Susanville, Cal. Lic. No. 249

Location of well: nw¼ nw¼ Sec. 2, T. 17N/S, R. 49E, in Nye County

or

Water will be used for Irrigation Total depth of well 200 ft

Size of drilled hole 28" Weight of casing per linear foot 36

Thickness of casing 8 Ga Kai-well Temp. of water

Diameter and length of casing 16" 200 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 85 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Dec 1 57 Date of completion of well Dec 23, 58

Type of well rig Rotary, and cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Soil.
6	24	18	Clay and gravel
24	34	10	Clay and Boulders
34	85	41	Clay.
85	98	13	Boulders and clay.
98	160	98	Clay.
160	174	14	Sand, boulders and clay.
174	200	26	Clay.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 160 to 174 ft.

Other aquifers 85 - 98

First water at 90 feet.

Casing perforated

from 90 to 200 ft.

Size of perforations

factory, 3/16 x 2.

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16	-0	200	200	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Test pumped approximatly 750 G.P.M. from 170 ft from surface.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Enloe Drilling Co.
Well Driller

By [signature]

License No. 249

Dated Feb. 21/58, 19

OFFICE
STATE ENGINEER
1958 MAR 5 AM 10 51

(Not to be filled in by Driller)

OFFICE
STATE ENGINEER
FEB 28 58
RECEIVED
ANS.