

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

C O P Y

Log No. 4032
 Rec. March 18 19 58
 Well No.
 Permit No.
Do not fill in

Owner Bureau of Land Management Driller Geo. W. Norcutt
 Address Carson City, Nevada Address Fallon, Nevada Lic. No. 93
 Location of well: NE 1/4 NE 1/4 Sec. 10., T19. N/S, R. 21. E. in Washoe County
 or
 Water will be used for winter sheep stock water Total depth of well 125'
 Size of drilled hole 6" Weight of casing per linear foot 12#
 Thickness of casing 3/16" Temp. of water
 Diameter and length of casing 5" O.D. 125'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well Jan. 14, 1958 Date of completion of well Feb. 20, 1958
 Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top soil
2	9	7	Hard pan
9	72	63	Gravel and boulders
72	96	24	Rock
96	97	1	Sand
97	116	19	Rock
116	125	9	Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 116' to 125' ft.

Other aquifers from 96' to 97'

First water at feet.

Casing perforated

from 105 to 125 ft.

Size of perforations

1/8" x 2"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed /s/ Geo. W. Norcutt
Well Driller

By.....

License No. 93

Dated March 1, 19 58

(Not to be filled in by Driller)

1958 MAR 18 AM 10 56

OFFICE
STATE ENGINEER