

21877

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. A062Rec. Apr 22 1958

Well No. \_\_\_\_\_

Permit No. 16955

Do not fill in

Owner RICHARD + HAROLD HEKZ Driller George Pounder  
 Address Box 444 Reno Nev Address Reno Nevada Lic. No. \_\_\_\_\_  
 Location of well: SE 1/4 SE 1/4 Sec 20, T.18 N. 8, R. 20 E, in W.H.S. Ho 2 County \_\_\_\_\_  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 50'

Size of drilled hole 6 inches Weight of casing per linear foot 5 pounds

Thickness of casing 3/8 inch Temp. of water Cold

Diameter and length of casing 6 3/4" - Length 70 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure None

If nonflowing well give depth of standing water from surface 50 ft.

If flowing well describe control works None  
 (Type and size of valve, etc.)

Date of commencement of well Oct. 11, 1953 Date of completion of well Nov. 3, 1953

Type of well rig Keystone Cable Tool

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	13	13	Sandy Soil - Boulder	
13	31	18	Sandy clay	Chief aquifer (water-bearing formation)
30	37	7	Sandy coarse gravel	from <u>65</u> to <u>200</u> ft.
37	55	18	Clay	Other aquifers _____
65	70	5	7 inch sand	_____
70	80	10	2 inch gravel	_____
				First water at <u>30</u> feet.
				Casing perforated
				from <u>24</u> to <u>70</u> ft.
				Size of perforations
				<u>5" by 4 inch</u>

