


WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA



Log No. 4094  
 Rec. June 12 1955  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

Do not fill in

Owner Pineforest Land & Stock Co. Driller Les Harvey

Address Winnemucca, Nevada Address Winnemucca, Nev. Lic. No. 170

Location of well: SW 1/4 Sec 22, T41N, R28E, in Humboldt County County

Water will be used for Stock Total depth of well 53 feet

Size of drilled hole 6" Weight of casing per linear foot 12.87 #

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 6" - 53 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 11 feet

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 10/14/57 Date of completion of well 10/17/57

Type of well rig Bucyrus Erie 24" Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	12	12	Sandy clay Topsoil	Chief aquifer (water-bearing formation) from <u>41</u> to <u>53</u> ft.
12	15	3	Sticky Bentonite clay	
15	18	3	Sand (water seep)	Other aquifers <u>15-18</u>
18	41	23	Sandy clay	
41	53	12	Sand & Gravel	

First water at 15 feet.

Casing perforated  
 from 30 to 50 ft.

Size of perforations  
3/16" x 6" Touch  
Cut Slots

