WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4114
Rec. June 20 1958
Well No.
Permit No. 18075
Do not fill in

Owner: Oscar Williams
Address: Sarcabatus Flats Scottys Jnc
Driller: W W Wright
Address: Dyer Nevada Lic. No. 56

Location of well: NW¼ NW¼ Sec. 14, T. 1 N/S, R. 44 E, in Nye County

or Sarcabatus Flats Scottys jnc on pitman act claim

Water will be used for: irrigation
Total depth of well: 270 ft

Size of drilled hole: 24"
Weight of casing per linear foot: part 20lb & 36

Thickness of casing: 3/16 & ½
Temp. of water: 58

Diameter and length of casing: 15" id 30 ft lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 73 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: May 17
Date of completion of well: June 6 58

Type of well rig: Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
top	65	65	alluvial volcanic
65	87	22	gravel & rock
87	105	18	gravel rock & clay
105	109	4	gravel
109	150	41	brown clay
150	182	32	gravel & rock
182	186	4	hard rock
186	194	8	gravel
194	210	16	clay & rock
210	214	4	clean gravel
214	235	21	clay & rock
235	270	35	volcanic formation contains small stratas of gravel.

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 65p to 87 ft.

Other aquifers 105 109
186 to 194
210 to 214

First water at 73 feet.

Casing perforated
from 73 to 270 ft.

Size of perforations
3/16 by 7" long

12 rows about 16" centers

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
15"	top	bottom	30 ft	15" 3/16 casing from top to 75 ft
				15" ¼" casing from 75 to bottom
				7" welded collars at every joint.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

~~well tested with 10" bowls 6" colum 150 ft setting~~
pump test 600 gpm draw down 9 ft

this well is gravel packed with a very good grade
~~of pea gravel.~~

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Wm S Wright sr Well Driller

By Wm S Wright sr

License No. 156

Dated June 23, 19 58

(Not to be filled in by Driller)

1958 JUN 26 AM 11 51

STATE ENGINEER
OFFICE

(OVER)