

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4115  
 Rec. June 26 1958  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Charles V. Stocke Driller M. Artlip

Address 339 Carrol Dr., Sun Valley, Nev. Address Sun Valley, Nev Lic. No. 287

Location of well: S.W. 1/4 NE 1/4 Sec 19, T. 32 N, R. 2 E, in Washoe County  
 or Lot 5 Block P. Sub. Div. # Sun Valley

Water will be used for Domestic Total depth of well 87'

Size of drilled hole 6" Weight of casing per linear foot 7 lbs.

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 6" by 80'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 27'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well April 21-58 Date of completion of well April 24--58

Type of well rig Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Sand and clay
40	48	8	Water bearing sand
48	70	22	Sandy clay
70	75	5	Coarse water sand
75	87	12	sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Coarse sand

---

Chief aquifer (water-bearing formation)  
 from 70 to 75 ft.

Other aquifers Water in all the sandy clay below 40 feet.

---

First water at 40 feet.

---

Casing perforated  
 from 40 to 80 ft.

---

Size of perforations  
4" by 3/8"



