

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4193
 Rec. July 31 1958
 Well No.
 Permit No.

Do not fill in

Owner Edward and Jean Anderson Driller Johnson & McNinch
 Address Winnemucca, Nevada Address Winnemucca Lic. No. 219

Location of well: 1/4 NE 1/4 Sec. 6, T35N/S, R38E, in Humboldt County
 or.....

Water will be used for Domestic Total depth of well 120'

Size of drilled hole 8" Weight of casing per linear foot 13 lbs.

Thickness of casing 10 gauge Temp. of water mild

Diameter and length of casing 8" 120'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 104'

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well June 8 1958 Date of completion of well June 18 1958

Type of well rig # 7I Speed Star Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	sandy soil
8	16	8	broken gravel
16	18	2	boulders
18	52	34	broken gravel and clay
52	80	28	boulders
80	105	25	clay and gravel
105	116	11	sand and large boulders
116	120	4	fine gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 105 to 120 ft.

Other aquifers.....

First water at 105 feet.

Casing perforated

from 100 to 120 ft.

Size of perforations
1/8 X 4" torch slots

