


WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA



Log No. 4205
 Rec. July 23 1958
 Well No. _____
 Permit No. _____
Do not fill in

Owner W. A. Rucker Driller Harvey & Bob Meyer
 Address General Delivery Steamboat, Nev. Address 306 Bath St. Carson Lic. No. 10
 Location of well: SE 1/4 SW 1/4 Sec. 4, T. 15 N/S, R. 20 E, in Washoe County
 or Steamboat Springs
 Water will be used for Domestic Total depth of well 100 feet
 Size of drilled hole 6 Inch Weight of casing per linear foot 13#
 Thickness of casing 3/16 Inch Temp. of water Cool
 Diameter and length of casing 6" ID, 100 feet
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing
 If nonflowing well give depth of standing water from surface 40 feet
 If flowing well describe control works Not Flowing
 (Type and size of valve, etc.)
 Date of commencement of well March 30, 1958 Date of completion of well April 12, 1958
 Type of well rig 72 Speed Star

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	31	31	Rock & Clay
31	38	7	Clay
38	76	38	Rock
76	78	2	Loose Rock
78	100	22	Rock & Sand

HARVEY & BOB MEYER
DRILLING CONTRACTORS
CARSON CITY, NEVADA

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 80 to 100 ft.

Other aquifers _____

First water at 76 feet.

Casing perforated

from 75 to 100 ft.

Size of perforations

1/8" X 6"

Torch



