

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4222
 Rec. Aug 7 19 58
 Well No.
 Permit No.

Do not fill in

Owner F.W. FELDER Driller M. Artlip

Address 170 E. 7th Ave., Sun Valley, Nev. Address 795 Lupin, Sun Valley Lic. No. 287

Location of well: NE 1/4 SE 1/4 Sec. 18, T. 20N/S, R. 20E, in Washoe County

or

Water will be used for Domestic Total depth of well 120'

Size of drilled hole 6" Weight of casing per linear foot 7 lb.

Thickness of casing 10 ga. Temp. of water cold

Diameter and length of casing 6" by 120
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 55'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well July 15 Date of completion of well July 17, 1958

Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	20	20	Hard sand
20	87	67	Sandy clay
87	90	3	Water sand
90	97	7	Hard sandy clay
97	100	3	Water sand
100	117	17	Sand & water clay
117	120	3	Hard sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Coarse sandy clay

Chief aquifer (water-bearing formation)

from 100 to 117 ft.

water ~~water~~

Other aquifers

sand 97 to 100'

..... 87 to 90'

First water at 87 feet.

Casing perforated

from 80 to 120 ft.

Size of perforations
1/16" by 6"



