

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4228  
 Rec. 9-B 19 58  
 Well No. \_\_\_\_\_  
 Permit No. 1777B  
*Do not fill in*



Owner Mr. Eichmeyer Driller \_\_\_\_\_

Address Lake Tahoe Subdivision Address \_\_\_\_\_ Lic. No. 257

Utility easement Between lots 24-25 \_\_\_\_\_

Location of well: 1/4 NE 1/4 Sec 23, T.13N/S, R.13 E, in Douglas County

or \_\_\_\_\_

Water will be used for Sub Division Total depth of well 50'

Size of drilled hole 14" Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 10 gauge Temp. of water Cold

Diameter and length of casing 14" 42'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well Aug. 12, 1958 Date of completion of well Aug. 23, 1958

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
(0)	5	5	Brown decomposed Gravel	Chief aquifer (water-bearing formation) from _____ to _____ ft.  Other aquifers _____    First water at <u>15</u> feet.  Casing perforated from _____ to _____ ft.  Size of perforations _____
5	10	5	" sand & "	
10	15	5	" decomposed granite	
15	20	5	Granite rocks & decomposed Granite	
20	25	5	Grey Granite Rock	
25	30	5	Broken rock granite	
30	35	5	Decomposed "	
35	40	5	" "	
40	45	5	Grey Granite Rocks Broken	
45	50	5	" " " "	

