

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4278
 Rec. Oct. 20 1958
 Well No.
 Permit No.

Do not fill in

Owner Eugene Przybyl Driller M. Artlip

Address 647 Stanford Way, Sparks Address Sun Valley, Nev. Lic. No 287

Location of well: NE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec 34, T20 N/S, R20 E, in Washoe County
 or

Water will be used for Domestic Total depth of well 70'

Size of drilled hole 6" Weight of casing per linear foot 7 lbs.

Thickness of casing 10ga. Temp. of water cold

Diameter and length of casing 6" X 60'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 19'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well Sept. 12 Date of completion of well Sept 15, 1958

Type of well rig cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
1	20	20	Soft Andacite	Chief aquifer (water-bearing formation) from <u>55</u> to <u>70</u> ft. 20 to 30 Other aquifers..... First water at <u>20</u> feet. Casing perforated from <u>45</u> to <u>60</u> ft. Size of perforations <u>1/16" X 10"</u>
20	55	35	dark andacite	
55	70	15	white andacite	



