

Replacement well  
**WELL LOG AND REPORT TO THE STATE  
 ENGINEER OF NEVADA**

Log No. 4225  
 Rec. Oct. 10 1958  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*

Owner Andyth Bingham Driller Maull Inc  
 Address Hiko, Nevada Address Pahrump, Nevada Lic. No. 50  
 Location of well: N. 1/4 S. 1/4 Sec. 30, T. 6 N/S, R. 1 E, in Lambton County  
 or 12' east of original hand dug well  
 Water will be used for Ordinary Total depth of well 31' 6"  
 Size of drilled hole 6" Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 3/8" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 6" - 27' 6"  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 15' 6"  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well October 6, 1958 Date of completion of well October 8, 1958  
 Type of well rig Hand Drill

**LOG OF FORMATIONS**

From feet	To feet	Thickness feet	Type of material
0	3	3	loose sand
0	12	9	firm sand
12	17	5	loose sand
17	21	4	firm sand
21	27	6	loose sand
27	31' 6"	4' 6"	sand with some clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 15 to 31 ft.

Other aquifers \_\_\_\_\_

First water at 15' 6" feet.

Casing perforated

from 16' 6" to 31' 6" ft.

Size of perforations

5/32 x 12"

