

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4330
 Rec. Nov. 21 19 58
 Well No.
 Permit No.

Do not fill in

Owner Domenico Natucci Driller Harvey & Bob Meyer
 Address 795 Roberts St. Reno, Nevada Address 306 Bath St. Carson ic. No. 10
 Location of well: NE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 23, T. 15N/S, R. 20E, in Ormsby County
 or Stewart Homesite
 Water will be used for Domestic Total depth of well 178
 Size of drilled hole 6" Weight of casing per linear foot 13#
 Thickness of casing 3/16" Temp. of water cool
 Diameter and length of casing 6" ID, 177 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not flowing
 If nonflowing well give depth of standing water from surface 71 feet
 If flowing well describe control works Not flowing
(Type and size of valve, etc.)
 Date of commencement of well July 24, 1958 Date of completion of well July 31, 1958
 Type of well rig 71-B Speed Star, Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	45	45	Sand	Chief aquifer (water-bearing formation)
45	80	35	Sand & Clay	from <u>175</u> to <u>178</u> ft.
80	125	45	Sandy clay w/ water	Other aquifers.....
125	150	25	Sand & Brown Clay	<u>110</u>
150	175	25	Hard Clay & Sand	
175	178	3	Water Sand	First water at <u>110</u> feet.
HARVEY & BOB MEYER DRILLING CONTRACTORS CARSON CITY, NEVADA				Casing perforated from <u>137</u> to <u>177</u> ft.
				Size of perforations <u>1/8" X 4"</u> Torch



