

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4335  
 Rec. Nov. 21 1958  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner Edward C. Auxier Driller Harvey Meyer  
 Address Topaz Lake Address Carson City Lic. No. 10  
 Location of well: NW 1/4 NE 1/4 Sec. 32., T. 19<sup>10</sup> N/S, R. 21<sup>22</sup> E. in Douglas County  
 or Topaz Lake, West Side  
 Water will be used for Domestic Total depth of well 70 feet  
 Size of drilled hole 6" Weight of casing per linear foot 13#  
 Thickness of casing 3/16" Temp. of water cool  
 Diameter and length of casing 6" ID, 70 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure not flowing  
 If nonflowing well give depth of standing water from surface 30 feet  
 If flowing well describe control works not flowing  
(Type and size of valve, etc.)  
 Date of commencement of well Sept 24, 1958 Date of completion of well Sept 26, 1958  
 Type of well rig 72 Speed Star Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	48	48	Clay-Rock	Chief aquifer (water-bearing formation) from <u>48</u> to <u>70</u> ft. Other aquifers..... ..... ..... ..... First water at <u>48</u> feet. Casing perforated from <u>67</u> to <u>70</u> ft. Size of perforations <u>1/8"</u>
48	70	22	Rock w/ water	
HARVEY & BOB MEYER DRILLING CONTRACTORS CARSON CITY NEVADA				

(OVER)



