Permit No. 15702

Log No. 4379
Rec. Jan 28 1959
Well No.
Permit No. 15702
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner P. J. Perry Driller Arnold Bowline

Address 11835 Gard Ave., Norwalk, Calif. Address Box 282, Lathrop Wells Lic. No. 279

Location of well: NE ¼ SE ¼ Sec. ~~23~~ 14, T 16 ~~N~~/S, R 48 E, in Nye County

or

Water will be used for IRRIGATION Total depth of well 240 ft.

Size of drilled hole 24 in. Weight of casing per linear foot 1/4 in.

Thickness of casing 1/4 in Temp. of water

Diameter and length of casing 12 in. 240 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 92 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well October 10, 1958 Date of completion of well November 26, 1958

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	"	90	Sandy Rock
90	"	95	Clay
95	"	110	Sandy & Gravel
110	"	128	Hard Pack Sand
128	"	146	Clay
146	"	164	Fine Sand
164	"	180	Clay
180	"	210	Sand & Gravel
210	"	228	Clay
228	"	240	Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 180 to 210 ft.

Other aquifers 95 - 110
228 - 240

First water at 92 feet.

Casing perforated
from 100 to 240 ft.

Size of perforations
3/16

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
12"			240	Gravel Pack

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

2800 G.P.M. @ 60 FT. 11-26-58. P.J. Levy

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Arnold Boulisu
Well Driller

By Boulisu Drilling

License No. 279

Dated Dec 18, 19 58

(Not to be filled in by Driller)

1959 JAN 28 AM 8 22
STATE ENGINEER
OFFICE