LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	63	63	Butt welded casing with drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail Test Approximately 13 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By J. W. Cunningham

License No. 4507

Dated July 10, 19 58

(Not to be filled in by Driller)

1959 MAR 2 PM 3 21
OFFICE
STATE ENGINEER

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4421
Rec. Mar. 2 1959
Well No.
Permit No.
Do not fill in

Owner: Wilfred Broussard Driller: J. N. Pitcher Company

Address: 2190 Prater Way Sparks Address: 190 Moana Lane Reno Lic. No. 1507

Location of well: SW 1/4 NW 1/4 Sec. 26, T. 20 N/S, R. 19 E, in Washoe County

or

Water will be used for: Domestic Total depth of well: 63'

Size of drilled hole: 6" Weight of casing per linear foot: 18 Lb.

Thickness of casing: 1/4" Temp. of water: 50°

Diameter and length of casing: 6" x 63'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 22'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: February 24, 1958 Date of completion of well: February 26, 1958

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	48	48	Brown clay Seep @ 28' W/gravel mottled
48	53	5	Broken rock--yellow & brown
53	63	10	Tight sand & gravel--water here

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 53 to 63 ft.

Other aquifers: Seep @ 28'

First water at 53 feet.

Casing perforated

from 43 to 63 ft.

Size of perforations

1/8" x 6" Torch Cut

919