

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 4427  
 Rec. Mar. 2 1959  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Mr. Al Koenig Driller J. N. Pitcher Company

Address 401 Flint St. Reno, Nevada Address 190 Moana Lane Reno Lic. No. 4507

Location of well: SW 1/4 S4 1/4 Sec. 22, T. 19 N/S, R. 19 E, in Washoe County

Water will be used for Domestic Total depth of well 460'

Size of drilled hole 6" Weight of casing per linear foot 18#

Thickness of casing 1/4" Temp. of water 91°

Diameter and length of casing 6" x 420'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 325'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well October 13, 1958 Date of completion of well October 31, 1958

Type of well rig Cable tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	23	23	Clay
23	110	87	Mixed Gravel & Sandy Clay
110	235	125	Sandy Clay and Gravel
235	350	115	Silt-Very Little Gravel -- water
350	425	75	Sand, Clay and Gravel
425	445	20	Gravel & Small Cobbles
445	460	15	Hard Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 235 to 350 ft.

Other aquifers \_\_\_\_\_

---

First water at 325 feet.

---

Casing perforated  
 from 325 to 420 ft.

---

Size of perforations  
1/4" Torch Cut & Mills Knife



