

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4447  
 Rec. Mar. 20 1959  
 Well No. ....  
 Permit No. ....

*Do not fill in*

Owner Mr. E. L. Betterton Driller Harvey & Bob Meyer  
 Address Star Route, Gardnerville, Nev. Address 306 Bath St. Carson Lic. No. 10  
 Location of well: SW 1/4 SE 1/4 Sec. 24, T10 N/S, R22 E, in Douglas County  
 or Topaz Lake  
 Water will be used for Domestic Total depth of well 70 feet  
 Size of drilled hole 6 Inch Weight of casing per linear foot 13 #  
 Thickness of casing 3/16" Temp. of water cool  
 Diameter and length of casing 6" ID, 62 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not Flowing  
 If nonflowing well give depth of standing water from surface 18 feet  
 If flowing well describe control works Not Flowing  
(Type and size of valve, etc.)  
 Date of commencement of well February 24, 1959 Date of completion of well March 6, 1959  
 Type of well rig 71-B Speed Star, Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Top Soil
6	55	49	Broken Rock
55	60	5	Broken Rock & Sand
60	70	10	Hard Rock

HARVEY & BOB MEYER  
 DRILLING CONTRACTORS  
 CARSON CITY, NEVADA

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 55 to 60 ft.

Other aquifers.....

---

First water at 55 feet.

Casing perforated  
 from 30 to 60 ft.

Size of perforations  
1/4" X 6"  
**Torch**



