WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4477
Rec. Apr. 8 1959
Well No.
Permit No.
Do not fill in

Owner Paul Candee Driller Fred Erb

Address Fallon Nevada Address East Star Route Fallon Nev Lic. No. 121

Location of well: NW ¼ SW ¼ Sec. 33, T. 19 N/S, R. 28 E, in Churchill County

or

Water will be used for Domestic Total depth of well 26 feet.

Size of drilled hole 6 inch Weight of casing per linear foot

Thickness of casing 20 gauge Galvinized Temp. of water 60°

Diameter and length of casing 6 inch Casing 26 ft long.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 9 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Mar. 5-1959 Date of completion of well Mar. 6, 1959

Type of well rig Cable Tool Well rig.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sand
8	9	1	adobe
9	12	3	Sand
12	20	8	adobe
20	26	6	Small Gravel

Water-bearing Formation, Casing Perforations, Etc.
Small Gravel

Chief aquifer (water-bearing formation)
from 20 to 26 ft.

Other aquifers

First water at 8 feet.

Casing perforated
from 20 to 26 ft.

Size of perforations
1 x 1/64 inch

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6in	0	26	26ft	20 gauge Galvinized Casing & well cap.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Pump Test about 1000 gallons per Hour.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Fred Eub
Well Driller

By Mrs. Fred Eub

License No. 121

Dated March 17, 1959

Contr Lic No. 4732

(Not to be filled in by Driller)

1959 APR 8 AM 9 01

STATE ENGINEER
OFFICE