LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	75	75	Butt welded casing with drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail Test Approximately 10 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By J. W. Cunningham

License No. 4507

Dated July 10, 1958

1959 APR 2 PM 1 50

OFFICE
ENGINEER

(Not to be filled in by Driller)

1959 APR 20 AM 10 58

OFFICE
ENGINEER

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4485
Rec. Apr. 20 19 59
Well No.
Permit No.
Do not fill in

Owner: Jones Driller: J. N. Pitcher Company

Address: Address: 190 Moana Lane Reno Lic. No. 4507

Location of well: ¼ ¼ Sec. 35, T. 20 N/S, R. 19 E, in Washoe County

or

Water will be used for: Domestic Total depth of well: 75'

Size of drilled hole: 6" Weight of casing per linear foot: 18 lb.

Thickness of casing: 1/4 Temp. of water: 55°

Diameter and length of casing: 6" x 75'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 18'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Date of completion of well:

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	Clay and boulders
35	55	20	Lava ash and clay
55	68	13	Broken rock
68	75	7	White clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 68 to 75 ft.

Other aquifers

First water at 68 feet.

Casing perforated

from to ft.

Size of perforations

1/8" x 6" Torch Cut

919