LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	95	95	Butt welded casing with drive shoe

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail Test approximately 20 GPM

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. N. Pitcher Company
Well Driller

By J. W. Cunningham

License No. 4507

Dated July 10, 1958, 19 58

1959 APR 2 PM 1 50

OFFICE
STATE ENGINEER

(Not to be filled in by Driller)

1959 APR 20 AM 10 58

OFFICE
STATE ENGINEER

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4490
Rec. Apr. 20 1959
Well No.
Permit No.
Do not fill in

Owner: J. W. Hunt — Driller: J. N Pitcher Company

Address: — Address: 190 Moana Lane — Lic. No. 4507

Location of well: ¼ ¼ Sec. 35, T. 20 N/S, R. 19 E, in Washoe County

or

Water will be used for: Domestic — Total depth of well: 95'

Size of drilled hole: 6" — Weight of casing per linear foot: 18 Lb.

Thickness of casing: 1/4" — Temp. of water: 55°

Diameter and length of casing: 6" x 95'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 50'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: March 25, 1958 — Date of completion of well: March 28, 1958

Type of well rig: Cable

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Surface clay and rock
8	82	74	Yellow Sandstone
82	95	13	Broken grey rock with water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 82 to 95 ft.

Other aquifers

First water at 82 feet.

Casing perforated

from 75 to 95 ft.

Size of perforations

1/8" x 6" Torch Cut

919