

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 4505
 Rec. Apr. 20 1959
 Well No. _____
 Permit No. _____

Do not fill in

Owner Mr. Martin Pesterfield Driller J. N. Fitcher Company

Address 7532 Mt. Rose Road Reno Address 190 Loana Lane Reno Lic. No. 1507

Location of well: 1/4 Sec. 1², T. 12 N/S, R. 19 E, in Washoe County

Water will be used for Domestic Total depth of well 140'

Size of drilled hole 6" Weight of casing per linear foot 20'

Thickness of casing 1/4" Temp. of water Cold

Diameter and length of casing 6" x 110'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 45'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Aug. 26, 1958 Date of completion of well Aug. 8, 1958

Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top soil and large boulders
3	10	7	Large granite boulders and gravel
10	22	12	Sandy stone
22	33	11	Fine sand and water
33	58	25	Sandy clay
58	63	5	Fine Sand
63	108	45	Sandy clay
108	112	4	Fine Sand
112	133	21	Course Semi Sand Very fine Sand
133	137	4	Course Semi Sand
137	140	3	Formation of rock

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 22 to 33 ft.

Other aquifers _____

First water at 22 feet.

Casing perforated

from 30 to 140 ft.

Size of perforations

1/4" Torch cut



